





200.33233



CABLE SLEEVES CAPABILITY

Size	hole diam.	cable diam.	
		min.	max
Small	10,5	11,0	13,5
Large	15,5	16,5	18,0

In	R ±2%
13A	1,5kΩ 0,5W
20A	680Ω 0,5W
32A	220Ω 0,5W

Description	A	Cross section	Torque
L1	14mm	2,5-6	0,8 Nm
L2	14mm	2,5-6	0,8 Nm
L3	14mm	2,5-6	0,8 Nm
N	14mm	2,5-6	0,8 Nm
⊕	14mm	2,5-6	0,8 Nm
CP	9mm	0,75-1,5	0,4 Nm
PP	9mm	0,75-1,5	0,4 Nm

SUGGESTION FOR CABLE

Type: S05BQ-F or equivalent
 Core insulation:
 EPR-rubber, crosslinked, type EI6
 Outer sheath:
 PUR, type TMPU flame-retardent
 Operating temperature:
 -40°C to +90°C

(*) SCREW TERMINALS

InfoTECH

ITALY

Numero Verde

800-018009





WORLDWIDE

Scame *OnLine*

www.scame.com

infotech@scame.com

200.33233



CABLE SLEEVES CAPABILITY

Size	hole diam.	cable diam.	
		min.	max
Small	10,5	11,0	13,5
Large	15,5	16,5	18,0

In	R ±2%
13A	1,5kΩ 0,5W
20A	680Ω 0,5W
32A	220Ω 0,5W

Description	A	Cross section	Torque
L1	14mm	2,5-6	0,8 Nm
L2	14mm	2,5-6	0,8 Nm
L3	14mm	2,5-6	0,8 Nm
N	14mm	2,5-6	0,8 Nm
⊕	14mm	2,5-6	0,8 Nm
CP	9mm	0,75-1,5	0,4 Nm
PP	9mm	0,75-1,5	0,4 Nm

SUGGESTION FOR CABLE

Type: S05BQ-F or equivalent
 Core insulation:
 EPR-rubber, crosslinked, type EI6
 Outer sheath:
 PUR, type TMPU flame-retardent
 Operating temperature:
 -40°C to +90°C

(*) SCREW TERMINALS

InfoTECH

ITALY

Numero Verde

800-018009

WORLDWIDE

Scame *OnLine*

www.scame.com

infotech@scame.com