

> DOMESTIC PLUGS AND SOCKETS



> VERSIONS



90° angled plugs.

Plugs with straight outlet.

Trailing sockets with straight outlet.

> REFERENCE STANDARDS

Italian standard CEI 23-50
Plugs and sockets for domestic and similar applications
Part 1: general requirements

IEC 60884-1
Plugs and socket-outlets for household and similar purposes
Part 1: general requirements

> QUALITY MARKS



> TECHNICAL CHARACTERISTICS

Rated current:	16A
Rated voltage:	250V~
Frequency:	50Hz
Insulating voltage:	250V~
Protection degree:	IP20D
Operating temperature according to the reference standard:	-15°C+35°C
Max. operating temperature:	60°C
Cabling capacity of the terminals:	10A: 0,75 - 1,5mm²
Glow Wire test:	750°C
Material:	Engineering plastic
Colour:	White RAL 9010

> BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Not Resistant	Not Resistant	Limited Resistance	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant	Resistant

> APPLICATION EXAMPLES

