

INDUSTRIAL ADAPTORS



VERSIONS

	One-way adaptors
	2-way adaptors with interlocked-switch socket outlets
	2-way adaptors
	3/5-way adaptors
	3-way adaptors with protection devices
	4-way adaptors










TECHNICAL CHARACTERISTICS

Rated current:	16A-32A
Frequency:	50Hz
Insulating voltage:	500/690V~
Protection degree:	IP20-IP44-IP66-IP67
Operating ambient temperature according to the reference standard:	-25°C +40°C
Max. operating ambient temperature:	60°C
Glow Wire test:	650°C/750°C/850°C
Material:	Engineering plastic
IK degree at 20°C:	IK06 - IK09

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Not Resistant	Not Resistant	Limited Resistance	Resistant	Not Resistant	Not Resistant	Not Resistant	Limited Resistance	Resistant	Resistant

AVAILABLE STANDARDS

 ITALIAN STANDARD P17/11 - 16A Shuttered socket CEI 23-50	 ITALIAN STANDARD P30 - 16A Shuttered socket CEI 23-50	 PLURISTANDARD P40 - 16A Shuttered socket CEI 23-50	 BRITISH STANDARD - 13A Shuttered socket BS 1363-2	 FRENCH STANDARD - 16A Shuttered socket NFC 61-314
 BRITISH STANDARD - 15A Shuttered socket BS 546	 ARGENTINIAN STANDARD - 10A Unshuttered socket IRAM 2071	 NEW ZEALAND STANDARD - 10A Unshuttered socket AS/NZS 3112	 SOUTH AFRICAN STANDARD - 16A Shuttered socket SANS 164:1 (2006)	

APPLICATION EXAMPLES

