

CONDUIT INSTALLATION ACCESSORIES - IP40



REFERENCE STANDARDS

- EN 61386-1**
Conduit system for cable management.
Part 1: general requirements.
- EN 61386-21**
Conduit system for cable management.
Part 2: particular requirements-rigid conduit systems.
- EN 60423**
Conduits for electrical installation.
External diameters of rigid,
are flexible conduits for electrical installations.

QUALITY MARKS



VERSIONS

- Inspection elbow
- Flat tee inspection
- Bend with two couplings
- Conduit coupling

TECHNICAL CHARACTERISTICS

Protection degree:	IP40
Operating ambient temperature according to the reference standard:	-5°C +60°C
Max. operating ambient temperature:	60°C
Glow Wire test:	750°C
IK degree at 20°C:	IK06-IK10
Material:	Engineering plastic
Colour:	Grey RAL 7035

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Resistant	Resistant	Resistant	Resistant	Limited Resistance	Limited Resistance	Resistant	Resistant	Resistant	Resistant

CONDUIT INSTALLATION ACCESSORIES - IP65



REFERENCE STANDARD

- EN 61386-1**
Conduit system for cable management.
Part 1: general requirements.
- EN 61386-21**
Conduit system for cable management.
Part 1: particular requirements-rigid conduit systems.
- EN 60423**
Conduits for electrical installation.
External diameters of rigid,
are flexible conduits for electrical installations.

QUALITY MARKS



VERSIONS

- Bend with two couplings
- 90° flexible bend
- Conduit couplings
- Conduit to box couplings
- Flexible joint for rigid-box tube connections
- Conduit to sheath couplings
- Sheat to box couplings
- Sheat to EUREKA couplings

TECHNICAL CHARACTERISTICS

Protection degree:	IP65
Operating ambient temperature according to the reference standard:	-5°C +60°C
Max. operating ambient temperature:	60°C
Glow Wire test:	750°C
IK degree at 20°C:	IK06-IK10
Material:	Engineering plastic
Colour:	Grey RAL 7035

CABLING OPERATIONS

