


Sockets for domestic applications

No. Reference SERIES


570




Versions




Panel mounting
flange 50x60mm
IP44



Panel mounting
flange 70x87mm
IP44



Panel mounting
flange 70x87mm
IP44



Surface mounting
flange 70x87mm
IP44

Reference standards

Standards: **CEI 23-50**
NFC 61-303
VDE 0620

Marking

Marking: **CE Marking** **CE**



Quality marks



TECHNICAL characteristics:

Rated current: **16A**
Rated voltage: **250V~**
Frequency: **50Hz**
Insulating voltage: **690V~**
Protection degree: **IP44 closed cover**
Operating temperature according to the reference standard: **-25°C+35°C**
Max. operating temperature: **60°C**
Glow Wire test: **650°C/750°C**
Material: **Engineering plastic**
IK degree at 20°C: **IK06**
Cabling capacity of the terminals: **1,5mmq ÷ 2x2,5mmq**

Main CHARACTERISTICS



Behaviour with CHEMICAL and ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
RESISTANT	NOT RESISTANT	NOT RESISTANT	LIMITED RESISTANCE	RESISTANT	NOT RESISTANT	NOT RESISTANT	NOT RESISTANT	LIMITED RESISTANCE	RESISTANT	RESISTANT