


Industrial adaptors

No. Reference SERIES


600 – 601 – 602 – 603 – 604 – 605
606 – 610 – 623 – 625




Versions




One-way adaptors




3/5-way adaptors




2-way adaptors with interlocked-switch socket outlets



3-way adaptors with protection devices



2-way adaptors



4-way adaptors

Reference standards

Standards: **EN 60670**

Marking

Marking: **CE Marking**



Quality marks



TECHNICAL characteristics:

Rated current: **16A-32A**
Frequency: **50Hz**
Insulating voltage: **500/690V~**
Protection degree: **IP20-IP40-IP44-IP66**
Operating temperature according to the reference standard: **-25°C+40°C**
Max. operating temperature: **60°C**
Glow Wire test: **650°C**
Material: **Engineering plastic**
IK degree at 20°C: **IK06-IK09**

*Handle and cable gland not supplied for elevated-installation versions.
The cable inlet is from below, where the adaptor is fastened to the stand.*



Behaviour with CHEMICAL and ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
RESISTANT	NOT RESISTANT	NOT RESISTANT	LIMITED RESISTANCE	RESISTANT	NOT RESISTANT	NOT RESISTANT	NOT RESISTANT	LIMITED RESISTANCE	RESISTANT	RESISTANT