

> DOMESTIC PLUGS, SOCKET AND MULTI-OUTLET SOCKETS



> VERSIONS

	Plugs with straight outlet
	Flat plugs with angle outlet
	Trailing socket with straight outlet
	Multi-outlet sockets

> REFERENCE STANDARDS

CEI 23-50
Plugs and sockets-outlets for household and similar purposes.
Part 1: general requirements

> QUALITY MARKS



> TECHNICAL CHARACTERISTICS

Rated current:	10A - 16A
Rated voltage:	250V~
Frequency:	50Hz
Insulating voltage:	250V~
Protection degree:	IP20D
Operating temperature according to the reference standard:	-15°C+35°C
Max operating temperature:	60°C
Cabling capacity of the terminals:	10A: 0,75 - 1,5mm² 16A: 0,75 - 2,5mm²
Glow wire test:	750°C
Material:	Engineering plastic
Colour:	White RAL 9010 Black RAL 9011 Anthracite RAL 7021 Tinted (transparent) Turquoise (transparent)

> BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistance	Resistant	Limited Resistance	Limited Resistance	Resistant	Not Resistant	Not Resistant	Resistant	Limited Resistance	Resistant

> APPLICATION EXAMPLES

