

> INNOVA < Series

Socket outlet – Non UK standard

No. REFERENCE SERIES

103.421


VERSIONS


Euro-american

REFERENCE STANDARDS
MARKING
QUALITY MARKS
TECHNICAL CHARACTERISTICS

Rated current: **16A**
 Rated voltage: **125V~/250V~**
 Frequency: **50Hz/60Hz**
 Insulating voltage: **250V~**
 Protection degree: **IP20**
 Operating temperature: **-5°C+40°C**
 Max operating temperature **+60°C**
 Glow Wire test: **850°C**
 Max. installation altitude: **2.000 m**
 Mounting box type : **Flush 1 gang (min. deepness: 25mm)**
 Surface 1 gang (min. deepness: 25mm)
 Material: **Engineering plastic**
 Colour: **White RAL 9016**

CABLING OPERATIONS
Cabling capacity of the terminals:

3x2,5 mm²
 3x4 mm²
 2x6 mm²

> INNOVA < Series

Socket outlet – Non UK standard


No. REFERENCE SERIES

103.421

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
RESISTANT	LIMITED RESISTANCE	RESISTANT	LIMITED RESISTANCE	RESISTANT	RESISTANT	NOT RESISTANT	NOT RESISTANT	RESISTANT	LIMITED RESISTANCE	RESISTANT

DIMENSIONS
Euro-american unswitched socket
