

> INTERLOCKED SWITCH SOCKET OUTLETS



> VERSIONS

	Flush mounting - with transformer - without transformer
	Surface mounting - without transformer

> REFERENCE STANDARDS

EN 60309-1
Plugs, socket outlets and couplers for industrial purposes
Part 1: general requirements

EN 60309-2
Plugs, socket outlets and couplers for industrial purposes
Part 2: dimensional interchangeability requirements for pin and contact-tube accessories of harmonised configurations

> QUALITY MARKS



> TECHNICAL CHARACTERISTICS

Rated current:	16A - 32A
Rated voltage:	20÷50V~
Frequency:	c.c. - 50÷60Hz
SELV transformer 220/24V:	150VA
Insulating voltage:	500/690V~
Protection degree:	IP44 - IP66/IP67
Operating temperature according to the reference standard:	-25°C+40°C
Max. operating temperature:	60°C
Glow Wire test:	650°C/850°C
Material:	Engineering plastic
IK degree at 20°C:	IK07 - IK08
Cable inlet:	PG/METRIC
Fuse-carriers:	gG 10,3x38 mm
Colour:	Grey RAL 7035

> BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Not Resistant	Resistant	Resistant	Resistant	Not Resistant	Not Resistant	Not Resistant	Limited Resistance	Resistant	Resistant

> WIRING AND INSTALLATION

Wiring capacity of the terminals (mm²)

Rated current (A)	Socket outlets	
	Min	Max
16A	4	10
32A	4	10

> APPLICATION EXAMPLES

