

> MULTI-OUTLET SOCKETS



> REFERENCE STANDARDS

IEC 60884-1
Plugs and socket-outlets for household and similar purposes
Part 1: general requirements

> VERSIONS

	Multi-outlet sockets without luminous switch
	Multi-outlet sockets with luminous switch
	Multi-outlet sockets with lighting protection

> TECHNICAL CHARACTERISTICS

Rated current:	16A
Rated voltage:	250V~
Frequency:	50Hz
Insulating voltage:	250V~
Protection degree:	IP20D
Operating temperature according to the reference standard:	-15°C+35°C
Max. operating temperature:	60°C
Glow Wire test:	750°C
Halogen free:	Yes
Cabling capacity of the terminal:	0,75÷2,5mm²
Material:	Engineering plastic
Colour:	White RAL 9010 Anthracite RAL 7021 Tinted (transparent) Turquoise blue (transparent)

> BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistance	Resistant	Limited Resistance	Limited Resistance	Resistant	Not Resistant	Not Resistant	Resistant	Limited Resistance	Resistant

> APPLICATION EXAMPLES

