

> CONDUIT INSTALLATION ACCESSORIES - IP40



> REFERENCE STANDARDS

<p>EN 61386-1 Conduit system for cable management <i>Part 1: general requirements</i></p>
<p>EN 61386-21 Conduit system for cable management <i>Part 1: particular requirements-rigid conduit systems</i></p>
<p>EN 60423 Conduits for electrical installation. External diameters of rigid are flexible conduits for electrical installations.</p>

> QUALITY MARKS



> VERSIONS

	Inspection elbow
	Flat tee inspection
	Bend with two couplings
	Conduit coupling

> TECHNICAL CHARACTERISTICS

Protection degree:	IP40
Operating temperature according to the reference standard:	-5°C+60°C
Max. operating temperature:	60°C
Glow Wire test:	750°C
IK degree at 20°C:	IK06-IK10
Material:	Engineering plastic
Colour:	Grey RAL 7035

> BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Resistant	Resistant	Resistant	Resistant	Limited Resistance	Limited Resistance	Resistant	Resistant	Resistant	Resistant

> APPLICATION EXAMPLES

