



TO ALL OUR CUSTOMERS

NEW

1. TOP22 SERIES MUSHROOM-HEAD PUSH-BUTTON – GENERAL USE

The mushroom pushbutton family of the TOP22 Series has been expanded with the version for general use (black/grey) Ø 90mm.



Thus a new catalogue number has been created.

DESCRIPTION	FEATURES	PACK QUANTITY	CATALOGUE NUMBER
IP66 General pushbutton - ø90mm	momentary	1/12	590.PG8M9W10

The product is supplied with a normally-open (NO) auxiliary contact assembled.

NEW

2. ROLLER 330 LAWN MOWER CABLE REEL

The SCAME cable reel product line has been extended with the new “lawn mower” versions.

This product has 1.5 m of cable (plug side) coming out of the plate and the rest of the cable (socket side) completely rewindable on the drum.







The cable reels have a protective device (thermal cut-out) incorporated to protect the cable from dangerous overheating, effective regardless of whether the cable is completely wound or unwound.





The following new catalogue numbers have thus been created.

The H05VV-F cable is used.

CABLE TYPE	LENGTH	MOBILE PLUG	MOBILE SOCKET	PACK QUANTITY	CATALOGUE NUMBER
3x2.5mm ²	30m	16A 2P+E (Italian S17)	16A 2P+E Pluristandard 	1	746.3005-894
3x1.5mm ²	30m	16A 2P+E (Italian S17)	16A 2P+E Pluristandard 	1	746.3005-895
3x1.5mm ²	40m	16A 2P+E (Italian S17)	16A 2P+E Pluristandard 	1	746.4005-895
3x1.5mm ²	40m	16A 2P+E (Italian S17)	16A 2P+E (P30) 	1	746.4005-896
3x1.5mm ²	40m	16A 2P+E (Italian S17)	10/16A 2P+E (P11/P17) 	1	746.4005-897
3x1.5mm ²	40m	16A 2P+E (French/German)	16A 2P+E (P30) 	1	746.4005-898

NEW

3. VERSIONS FOR RUBBER SERIES DISTRIBUTION PANELS

The SCAME product line of panels now includes Rubber distribution assemblies in the new empty versions and wired versions on request. These are particularly convenient in demanding applications requiring superior mechanical strength and chemical resistance such as public performances, shipyards and mines.

The main technical characteristics are the following:

- IK09 Impact resistance (wired versions)
- IK10 Impact resistance (empty versions)
- Excellent mechanical resistance of the cases against impacts, traction and crushing
- Butyl rubber resistant to oils, acids, benzene and industrial solvents
- Excellent ageing resistance
- Temperature range: – 40°C to + 60°C
- Cover fastening screws in stainless steel on die-cast brass inserts in the rubber
- Socket retaining screws in stainless steel with insulated head
- Switchboards in transparent polycarbonate with return spring in stainless steel

See the general catalogue for more information.





DESCRIPTION	CATALOGUE NUMBER
Type B, Model H10, dimensions 400x400x275	692.4201-00
Type C, Model Beta, dimensions 235x234x180	692.4202-00
Type D, Model Omega, dimensions 295x295x280	692.4203-00
Type E, Model TAU, dimensions 210x260x98	692.4204-00
Type F, Model rectangle, dimensions 450x130x83	692.4205-00
Type G, Model Prisma, dimensions 230x130x170	692.4206-00

SCAME PARRE S.p.A.
MARKETING OFFICE