



## TO SCAME CLIENTS

### List of new available products

(Refer to Commercial Dept for item codes and prices)

#### ISOLATORS-EX Series

- ISOLATORS Series – HD Version (ATEX Ex)
- ISOLATORS Series – Emergency Version (ATEX Ex)



The Safety Switch suitable for the category 2D, zone 21 and 22, they obtained the upgrade at the following new standards (dust) EN 60079-31.

#### ADVANCE-GRP Series

- ADVANCE-GRP Series Version (ATEX Ex)  
*only from 16A to 63A*
- OPTIMA-EX Series Version (ATEX Ex)  
*only from 16A to 63A*



The socket Interlock-switch suitable for the category 2D, zone 21 and 22, they obtained the upgrade at the following new standards (dust) EN 60079-31.



## ISOLATORS-EX[GD] Series

- ISOLATORS-Ex[GD] Series – HD Version  
GRP-Aluminium-Inox (ATEX – IEC-Ex)
- Serie ISOLATORS-Ex[GD] – Emergency Version  
GRP-Aluminium-Inox (ATEX – IEC-Ex)



SCAME offers the appropriate switch disconnecter (**series 591**) even for the most demanding environments as explosive atmosphere. The enclosures will be available in strong, high quality materials as GRP, Aluminium, and Stainless Steel sheet and acid-proof material.

To ensure corrosion resistance in difficult operating conditions, all the switches disconnector starting from 16 A to 63 A.

The hazardous area switch disconnecter enclosures are supplied with 3 large cable entries which can be fitted with approved hazardous area reducers to suit individual cable requirements. All ISOLATORS-EX[GD] are equipped by switching safety-switch certified as component ATEX and IEC-Ex and have contacts as **2P, 3/4P+T** (switched neutral) also **have AC22A - AC23A** ratings - auxiliary contacts are available for various applications within a breather/drain valve as accessory on demands.

## ENERBOX Series

Distribution assemblies



### ■ 6 DIN distribution assemblies – IP55

DIN modules	Dimensions (mm)	Dissipated power	Front knockouts	Side knockouts	Pack Qty.	Catalogue number
6 DIN	285x145x107	9W	Blank plate	4 closed	1	633.1010
			1x16/32A	2 open – 2 closed	1	633.1011
			1x63A	2 open – 2 closed	1	633.1012

### ■ 11 DIN distribution assemblies – IP55

DIN modules	Dimensions (mm)	Dissipated power	Front knockouts	Side knockouts	Pack Qty.	Catalogue number
11 DIN	285x235x107	15W	Blank plate	4 closed	1	633.2020
			2x16/32A	2 open – 2 closed	1	633.2021
			2x63A	2 open – 2 closed	1	633.2022
			1x16/32A + 1x63A	2 open – 2 closed	1	633.2023



## LIBERA Series

■ New type 2 sockets



### With shutter

First Type 2 sockets on market with integrated shutter. Available even without shutter.



### Compact

Scame version of Type 2 socket without shutter in alternative at competitors.



### Accessories

Motorized latching system.  
Lids.



■ New Wallbox

### With type 2 socket with shutter

First station on market with Type 2 socket with shutter.



### With tethered cable

Solution for domestic applications.



### P Series

Simplified version of R Series for cost containment in domestic applications. Without rfid and metering, with protections.

### E Series

Simplified version of L Series for cost containment in domestic applications. Without rfid, metering and protections.

■ New mode 4 stations

### Mobile

With Chademo and Combo 2 20kW. Compared to a 50kW station time increases only 10 minutes more.



### Combined

Mode 4 + Mode 3. With Chademo and Combo 2 20kW, Type 2 socket 22kW. Compared to a 50kW station time increases only 10 minutes more.



Products available.

Further information: *ECOMOBILITY catalogue 2015-2016 forthcoming.*