



## 247.32964

# FLUSH MOUNTING APPLIANCE INLET

32A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz  
60Hz 70X87MM Screw terminals

Product Approvals

| TECHDATA                   |                                | STANDARDS AND LAWS                |   |
|----------------------------|--------------------------------|-----------------------------------|---|
| Type of product            | FLUSH MOUNTING APPLIANCE INLET | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Commercial series          | EUREKA Series                  | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description    | FLUSH MOUNTING APPLIANCE INLET |                                   |   |
| Mounting version           | FLUSH/SURFACE MOUNTING         | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Rated current              | 32A                            | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Poles                      | 3P+E                           |                                   |   |
| Hour position              | 3h                             | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Rated voltage (range)      | 250-400V                       |                                   |   |
| Rated voltage              | 380V 50Hz / 440V 60Hz          |                                   |   |
| Working frequency          | 60Hz                           |                                   |   |
| Working frequency          | 50Hz                           |                                   |   |
| Colour                     | RED                            |                                   |   |
| Material                   | THERMOPLASTIC                  |                                   |   |
| Protection degree          | Watertight                     |                                   |   |
| Protection degree IP       | IP66/IP67                      |                                   |   |
| Types of available outlets | 90° ANGLED                     |                                   |   |
| Terminals                  | Screw terminals                |                                   |   |

|              |         |
|--------------|---------|
| Flange       | 70X87MM |
| Cable outlet | PG 16   |