

Product Technical Sheet

20 Oct 2021 03:54



504.125866.RU

INTERLOCKED SOCKET

125A 3P+E 7h 480-500V 50Hz 60Hz II 2GD
Screw terminals With mechanical interlock EAC
[Eurasian Conformity]

Product Approvals

TECHDATA

Commercial series	ADVANCE-GRP[GD] Series
Type of product	INTERLOCKED SOCKET
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING
Rated current	125A
Poles	3P+E
Hour position	7h
Rated voltage (range)	400-up
Rated voltage	480-500V
Working frequency	60Hz
Working frequency	50Hz
Colour	BLACK
Material	GRP Glass Reinforced Polyester
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	IK10
Terminals	Screw terminals
Contact material	CuZn (brass)

Cable entry	1xM50
Working temperature	-40°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Group and categories EX	II 2GD
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Options	EAC [Eurasian Conformity]
Options	With mechanical interlock
Padlock	ø6,3mm