



# 504.16834-A.RU

## INTERLOCKED SOCKET

16A 2P+E 3h >50-250V DC II 2GD  
 130X260MM\_PAR With mechanical interlock  
 EAC [Eurasian Conformity] Low temperature  
 [-50°C]

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE-GRP[GD] Series	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Type of product	INTERLOCKED SOCKET		
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	16A		
Poles	2P+E		
Hour position	3h		
Rated voltage (range)	50-200V		
Rated voltage	>50-250V		
Working frequency	DC		
Colour	RED		
Material	GRP Glass Reinforced Polyester		
Protection degree	Splash proof		
Protection degree IP	IP66		
Flange	130X260MM_PAR		
Cable outlet	1xM25		
Group and categories EX	II 2GD		
Ambient temperature Ta min	-50 °C		

Ambient temperature Ta max	60 °C
Options	Low temperature [-50°C]
Options	EAC [Eurasian Conformity]
Options	With mechanical interlock
Padlock	ø5mm