

Product Technical Sheet

17 May 2022 08:05



504.6374.RU

INTERLOCKED SOCKET

63A 3P+E 9h 200-250V 50Hz 60Hz II 2GD
170X380MM_PAR Screw terminals With
mechanical interlock EAC [Eurasian Conformity]

Product Approvals

TECHDATA

Type of product	INTERLOCKED SOCKET
Commercial series	ADVANCE-GRP[GD] Series
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING
Rated current	63A
Poles	3P+E
Hour position	9h
Rated voltage (range)	200-250V
Rated voltage	200-250V
Working frequency	60Hz
Working frequency	50Hz
Colour	BLUE
Material	GRP Glass Reinforced Polyester
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	IK10
Terminals	Screw terminals
Contact material	CuZn (brass)

Flange	170X380MM_PAR
Cable entry	1xM40
Working temperature	-35°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Group and categories EX	II 2GD
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Options	With mechanical interlock
Options	EAC [Eurasian Conformity]
Padlock	ø6,3mm