

## MULTI-OUTLET SOCKETS



## REFERENCE STANDARDS

**IEC 60884-1**  
Plugs and socket-outlets for household and similar purposes.  
*Part 1: general requirements.*

**CEI 23-124**  
Plugs and socket outlets for household and similar purposes.  
*Part 2-7: particular requirements for cord extension set.*

**CEI 23-50**  
Plugs and sockets for domestic and similar applications.  
*Part 1: general requirements.*

## VERSIONS

	Multi-outlet sockets without luminous switch
	Multi-outlet sockets with luminous switch
	Multi-outlet sockets with lighting protection

## TECHNICAL CHARACTERISTICS

Rated current:	<b>16A</b>
Rated voltage:	<b>250V~</b>
Frequency:	<b>50Hz</b>
Insulating voltage:	<b>250V~</b>
Protection degree:	<b>IP20D</b>
Operating ambient temperature according to the reference standard:	<b>-15°C +35°C</b>
Max. operating ambient temperature:	<b>60°C</b>
Glow Wire test:	<b>750°C</b>
Halogen free:	<b>Yes</b>
Cabling capacity of the terminal:	<b>0,75±2,5mm<sup>2</sup></b>
Material:	<b>Engineering plastic</b>
Colour:	<b>Random (*) Anthracite RAL 7021 Tinted (transparent) Turquoise blue (transparent)</b>

(\*) Random colour means casual "white base - grey lid" or "grey base - white lid".

## BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistance	Resistant	Limited Resistance	Limited Resistance	Resistant	Not Resistant	Not Resistant	Resistant	Limited Resistance	Resistant

## APPLICATION EXAMPLES

