

## CONDUIT INSTALLATION ACCESSORIES



## VERSIONS

	90° bend
	Conduit coupling
	Conduit to box coupling
	Conduit to box couplings (equal diameter)

## REFERENCE STANDARDS

**EN 61386-1**  
Conduit systems for cable management.  
*Part 1: general requirements.*

**EN 61386-21**  
Conduit systems for cable management.  
*Part 2: particular requirements - rigid conduit systems.*

## QUALITY MARKS



## TECHNICAL CHARACTERISTICS

Protection degree:	<b>IP66/IP67</b>
Operating ambient temperature according to the reference standard:	<b>-5°C +60°C</b>
Max operating ambient temperature:	<b>60°C</b>
Glow wire test:	<b>750°C</b>
Halogen free:	<b>Yes</b>
IK degree at 20°C:	<b>IK07-IK10</b>
Material:	<b>Engineering plastic</b>
Colour:	<b>Grey RAL 7035</b>

## BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Resistant	Resistant	Resistant	Resistant	Limited Resistance	Limited Resistance	Resistant	Resistant	Limited Resistance	Resistant

## CO-INJECTION MOULDED GASKET



The use of a co-injection moulding system makes it possible to turn the technopolymer gasket into an extension of the piece and disguise it as part of the pipe. It also provides a greater degree of sealing efficiency and makes it easier to insert pipe fittings without squashing or deforming the gasket.

## APPLICATION EXAMPLES

