

## CONDUIT INSTALLATION ACCESSORIES - IP40



## REFERENCE STANDARDS

- EN 61386-1**  
Conduit system for cable management.  
*Part 1: general requirements.*
- EN 61386-21**  
Conduit system for cable management.  
*Part 2: particular requirements-rigid conduit systems.*
- EN 60423**  
Conduits for electrical installation.  
External diameters of rigid, are flexible conduits for electrical installations.

## QUALITY MARKS



## VERSIONS

- Inspection elbow
- Flat tee inspection
- Bend with two couplings
- Conduit coupling

## TECHNICAL CHARACTERISTICS

Protection degree:	<b>IP40</b>
Operating ambient temperature according to the reference standard:	<b>-5°C +60°C</b>
Max. operating ambient temperature:	<b>60°C</b>
Glow Wire test:	<b>750°C</b>
IK degree at 20°C:	<b>IK06-IK10</b>
Material:	<b>Engineering plastic</b>
Colour:	<b>Grey RAL 7035</b>

## BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Resistant	Resistant	Resistant	Resistant	Limited Resistance	Limited Resistance	Resistant	Resistant	Resistant	Resistant

## CONDUIT INSTALLATION ACCESSORIES - IP65



## REFERENCE STANDARD

- EN 61386-1**  
Conduit system for cable management.  
*Part 1: general requirements.*
- EN 61386-21**  
Conduit system for cable management.  
*Part 1: particular requirements-rigid conduit systems.*
- EN 60423**  
Conduits for electrical installation.  
External diameters of rigid, are flexible conduits for electrical installations.

## QUALITY MARKS



## VERSIONS

- Bend with two couplings
- 90° flexible bend
- Conduit couplings
- Conduit to box couplings
- Flexible joint for rigid-box tube connections
- Conduit to sheath couplings
- Sheat to box couplings
- Sheat to EUREKA couplings

## TECHNICAL CHARACTERISTICS

Protection degree:	<b>IP65</b>
Operating ambient temperature according to the reference standard:	<b>-5°C +60°C</b>
Max. operating ambient temperature:	<b>60°C</b>
Glow Wire test:	<b>750°C</b>
IK degree at 20°C:	<b>IK06-IK10</b>
Material:	<b>Engineering plastic</b>
Colour:	<b>Grey RAL 7035</b>

## CABLING OPERATIONS

